



XE-MINI/ED PLUS SERIES

Go where others can't – 5.4 m / 6.4 m working height in a 0.76 m width

Standard Features

- Proportional Controls
- Self-lock gate on platform
- Extended Platform
- Drivable at full height
- Non-marking Tires
- 4 x 2WD
- Automatic brake system
- Emergency lowering system
- Emergency stop button
- Explosion-proof of the tubing
- Diagnosis system
- Tilt sensor with Alarm
- Horn
- Flash light
- Hour meter
- Safety Brackets
- Forklift Pockets

Options Features

- Overload sensor
- AC power to platform



Ultra-Compact Electric Scissors

Specifications

Models	XE50MINI/ED PLUS	XE59MINI/ED	XE60MINI/ED PLUS
--------	------------------	-------------	------------------

Measurements

A Max. Working Height	5.4m	5.9m	6.4m
B Max. Platform Height	3.4m	3.9m	4.4m
C Max. Outreach	0.55m	0.55m	0.55m
D Length Stowed	1.49m	1.49mm	1.49m
E Length - Platform Extension	1.8m	1.8m	1.8m
F Width Stowed	0.76m	0,76m	0.76m
G Height Stowed (guardrails unfolded)	1.95m	2.03m	2.17m
H Height Stowed (guardrails folded)	1.5m	1.59m	1.72m
I Wheelbase	1.05m	1.05m	1.05m
J Ground Clearance	0.06m	0.06m	0.06m
K Pothole protection board ground Clearance(down)	0.015m	0.015m	0.015m
Platform Size(LxWxH)	1.28mx0.76mx1.1m	1.28mx0.76mx1.1m	1.28mx0.76mx1.1m
L Skirting Board Height	0.17m	0.17m	0.17m

Productivity

Max. Load number (indoor)	2pers	2pers	2pers
Lifting Capacity	240kg	240kg	240kg
Lifting Capacity (extended platform)	100kg	100kg	100kg
Drive Speed (Seowed)	3km/h	3km/h	3km/h
Drive Speed (Raised)	0.7km/h	0.7km/h	0.7km/h
Rising Time	20s	20s	23s
Lowering Time	17s	17s	19s
Gradeability	25%	2pers	25%
Turing Radius - inside	0.35m/1.02m	0.35m/1.02m	0.35m/1.02m
Tilt Sensor - Front to Back	3°	3°	3°
Tilt Sensor - Side to Side	1.5°	1.5°	1.5°
Tires - solid non-marking	230mm	230mm	230mm

Power

Drive Mode	Electric, 2WD×2WS	Electric, 2WD×2WS	Electric, 2WD×2WS
Power Unit Motor (voltage/power)	24V/0.8kw	24V/0.8kw	24V/0.8kw
Hydraulic Tank Capacity	2L	2L	2L
Battery Specifications	114Ah	114Ah	114Ah
Control Voltage	24V	24V	24V
Charger (Input Voltage/Output Current)	100-240V/15A	100-240V/15A	100-240V/15A

Weight

Weight	860kg	930kg	930kg
Standard	CE/GB	CE/GB	CE/GB

