

XE-CT SERIES
XE59CT OR/ XE59CT
CRAWLER TYPE SCISSOR LIFT

Product Highlights

Efficient and flexible

- ★ Joystick control for turning and walking, easy to operate
- ★ Can turn unilaterally and in place, with flexible maneuverability
- ★ Supports one button automatic leveling, strong adaptability to the venue, safe

Excellent performance

- ★ Rubber tracked chassis, suitable for various complex road surfaces
- ★ Maintenance-free battery with strong battery life
- ★ Electric drive, zero emissions, high efficiency

Low operating costs

- ★ Drawer type structure, convenient and fast maintenance and repair of key components
- ★ Faults diagnosis system, intelligent and efficient



Standard Features

Tilt alarm system	Charging indicator	Buzzer
Diagnosis system	AC power to platform	Flash light
Explosion-proof of the tubing	Manual box	Fault code display
Automatic brake system	Emergency lower	Motion alarm
Safety Support Bar	Manual brake release	Forklift and lifting holes
Non-marking rubber crawler	Maintenance free battery	
Hour meter, battery display	Proportional Control	

Options Features

Top stop sensor	GPS	Electrophoretic coating process
Overload sensor	Platform work light	
Power socket to platform	Foot switch	


XE-CT SERIES

XE59CT OR/ XE59CT

CRAWLER TYPE SCISSOR LIFT

Model	XE59CT OR	XE59CT
Dimension		
Max. Working Height	5.9m	5.9m
A Max. Platform Height	3.9m	3.9m
B Max. Outreach	0.9m	0.9m
C Length Stowed	2.167m	2.027m
D Width Stowed	1.104m	1.022m
Height Stowed (guardrails folded)	1.78m	1.78m
E Height Stowed (guardrails unfolded)	2.15m	2.15m
Ground Clearance	0.16m	0.16m
Platform Size(L×W×H)	1.85m×0.89m×1.1m	1.85m×0.89m×1.1m
Crawler Size	Y200×72-49Section	Y200×72-49Section
Performance		
Lifting Capacity	230kg	230kg
Lifting Capacity (extended platform)	115KG	115KG
Max. Load number	2pers	2pers
Drive Speed	1.7km/h	1.7km/h
Rising Time	32s	32s
Lowering Time	30s	30s
Gradeability	40%	40%
Tilt Sensor (front to back)	3°	3°
Tilt Sensor (side to side)	1.5°	1.5°
Outrigger level ability - front to back/ side to side	4.5°/10°	4.5°/10°
Max. Lateral Force	400N	400N
Max. Wind Speed	12.5m/s	12.5m/s
Power		
Power Unit Motor (voltage/power)	24V/2.2kW	24V/2.2kW
Hydraulic Tank Capacity	7L	7L
Battery Specifications	4×6V;200Ah	4×6V;200Ah
System Voltage	24V	24V
Control Voltage	24V	24V
Charger (Input Voltage/Output Current)	96-265V/30A	96-265V/30A
Drive motor (voltage/power)	15VAC/1kW	15VAC/1kW
Drive mode	Electric	Electric
Weight		
Weight	1608kg	1408kg
Standard	GB/CE	

XE-CT



XE-CT

